

**ISSN 2518-1491 (Online),
ISSN 2224-5286 (Print)**

ҚАЗАҚСТАН РЕСПУБЛИКАСЫ
ҰЛТТЫҚ ҒЫЛЫМ АКАДЕМИЯСЫНЫҢ

Д.В.Сокольский атындағы «Жанармай,
катализ және электрохимия институты» АҚ

Х А Б А Р Л А Р Ы

ИЗВЕСТИЯ

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК
РЕСПУБЛИКИ КАЗАХСТАН
АО «Институт топлива, катализа и
электрохимии им. Д.В. Сокольского»

NEWS

OF THE ACADEMY OF SCIENCES
OF THE REPUBLIC OF KAZAKHSTAN
JSC «D.V. Sokolsky institute of fuel, catalysis
and electrochemistry»

**SERIES
CHEMISTRY AND TECHNOLOGY**

1 (439)

JANUARY – FEBRUARY 2020

PUBLISHED SINCE JANUARY 1947

PUBLISHED 6 TIMES A YEAR

ALMATY, NAS RK

NAS RK is pleased to announce that News of NAS RK. Series of chemistry and technologies scientific journal has been accepted for indexing in the Emerging Sources Citation Index, a new edition of Web of Science. Content in this index is under consideration by Clarivate Analytics to be accepted in the Science Citation Index Expanded, the Social Sciences Citation Index, and the Arts & Humanities Citation Index. The quality and depth of content Web of Science offers to researchers, authors, publishers, and institutions sets it apart from other research databases. The inclusion of News of NAS RK. Series of chemistry and technologies in the Emerging Sources Citation Index demonstrates our dedication to providing the most relevant and influential content of chemical sciences to our community.

Қазақстан Республикасы Ұлттық ғылым академиясы "ҚР ҰҒА Хабарлары. Химия және технология сериясы" ғылыми журналының Web of Science-тің жаңаланған нұсқасы Emerging Sources Citation Index-те индекстелуге қабылданғанын хабарлайды. Бұл индекстелу барысында Clarivate Analytics компаниясы журналды одан әрі the Science Citation Index Expanded, the Social Sciences Citation Index және the Arts & Humanities Citation Index-ке қабылдау мәселесін қарастыруды. Web of Science зерттеушілер, авторлар, баспашилар мен мекемелерге контент тереңдігі мен сапасын ұсынады. ҚР ҰҒА Хабарлары. Химия және технология сериясы Emerging Sources Citation Index-ке енүі біздің қоғамдастық үшін ең өзекті және беделді химиялық ғылымдар бойынша контентке адалдығымызды білдіреді.

НАН РК сообщает, что научный журнал «Известия НАН РК. Серия химии и технологий» был принят для индексирования в Emerging Sources Citation Index, обновленной версии Web of Science. Содержание в этом индексировании находится в стадии рассмотрения компанией Clarivate Analytics для дальнейшего принятия журнала в the Science Citation Index Expanded, the Social Sciences Citation Index и the Arts & Humanities Citation Index. Web of Science предлагает качество и глубину контента для исследователей, авторов, издателей и учреждений. Включение Известия НАН РК в Emerging Sources Citation Index демонстрирует нашу приверженность к наиболее актуальному и влиятельному контенту по химическим наукам для нашего сообщества.

Бас редакторы

х.ғ.д., проф., КР ҰҒА академигі
М.Ж. Жұрынов

Редакция алқасы:

Агабеков В.Е. проф., академик (Белорус)
Волков С.В. проф., академик (Украина)
Воротынцев М.А. проф., академик (Ресей)
Газалиев А.М. проф., академик (Қазақстан)
Ергожин Е.Е. проф., академик (Қазақстан)
Жармағамбетова А.К. проф. (Қазақстан), бас ред. орынбасары
Жоробекова Ш.Ж. проф., академик (Қырғыстан)
Иткулова Ш.С. проф. (Қазақстан)
Манташян А.А. проф., академик (Армения)
Пралиев К.Д. проф., академик (Қазақстан)
Баешов А.Б. проф., академик (Қазақстан)
Бұркітбаев М.М. проф., академик (Қазақстан)
Джусипбеков У.Ж. проф. корр.-мүшесі (Қазақстан)
Молдахметов М.З. проф., академик (Қазақстан)
Мансуров З.А. проф. (Қазақстан)
Наурызбаев М.К. проф. (Қазақстан)
Рудик В. проф., академик (Молдова)
Рахимов К.Д. проф. академик (Қазақстан)
Стрельцов Е. проф. (Белорус)
Тәшімов Л.Т. проф., академик (Қазақстан)
Тодераш И. проф., академик (Молдова)
Халиков Д.Х. проф., академик (Тәжікстан)
Фарзалиев В. проф., академик (Әзірбайжан)

«ҚР ҰҒА Хабарлары. Химия және технология сериясы».

ISSN 2518-1491 (Online)

ISSN 2224-5286 (Print)

Меншіктенуші: «Қазақстан Республикасының Үлттық ғылым академиясы» Республикалық қоғамдық бірлестігі (Алматы қ.)

Қазақстан республикасының Мәдениет пен ақпарат министрлігінің Ақпарат және мұрагат комитетінде 30.04.2010 ж. берілген №1089-Ж мерзімдік басылым тіркеуіне қойылу туралы куәлік

Мерзімділігі: жылдан 6 рет.

Тиражы: 300 дана.

Редакцияның мекенжайы: 050010, Алматы қ., Шевченко көш., 28; 219, 220 бөл.; тел.: 272-13-19; 272-13-18,
<http://chemistry-technology.kz/index.php/en/arhiv>

© Қазақстан Республикасының Үлттық ғылым академиясы, 2020

Типографияның мекенжайы: «NurNaz GRACE», Алматы қ., Рысқұлов көш., 103.

Г л а в н ы й р е д а к т о р

д.х.н., проф., академик НАН РК
М. Ж. Журинов

Р е д а к ц и о н н а я к о л л е г и я:

Агабеков В.Е. проф., академик (Беларусь)
Волков С.В. проф., академик (Украина)
Воротынцев М.А. проф., академик (Россия)
Газалиев А.М. проф., академик (Казахстан)
Ергожин Е.Е. проф., академик (Казахстан)
Жармагамбетова А.К. проф. (Казахстан), зам. гл. ред.
Жоробекова Ш.Ж. проф., академик (Кыргызстан)
Иткулова Ш.С. проф. (Казахстан)
Манташян А.А. проф., академик (Армения)
Пралиев К.Д. проф., академик (Казахстан)
Баешов А.Б. проф., академик (Казахстан)
Буркитбаев М.М. проф., академик (Казахстан)
Джусипбеков У.Ж. проф. чл.-корр. (Казахстан)
Мулдахметов М.З. проф., академик (Казахстан)
Мансуров З.А. проф. (Казахстан)
Наурызбаев М.К. проф. (Казахстан)
Рудик В. проф., академик (Молдова)
Рахимов К.Д. проф. академик (Казахстан)
Стрельцов Е. проф. (Беларусь)
Ташимов Л.Т. проф., академик (Казахстан)
Тодераш И. проф., академик (Молдова)
Халиков Д.Х. проф., академик (Таджикистан)
Фарзалиев В. проф., академик (Азербайджан)

«Известия НАН РК. Серия химии и технологии».

[ISSN 2518-1491 \(Online\)](#)

[ISSN 2224-5286 \(Print\)](#)

Собственник: Республиканское общественное объединение «Национальная академия наук Республики Казахстан» (г. Алматы)

Свидетельство о постановке на учет периодического печатного издания в Комитете информации и архивов Министерства культуры и информации Республики Казахстан №10893-Ж, выданное 30.04.2010 г.

Периодичность: 6 раз в год

Тираж: 300 экземпляров

Адрес редакции: 050010, г. Алматы, ул. Шевченко, 28; ком. 219, 220; тел. 272-13-19; 272-13-18,
<http://chemistry-technology.kz/index.php/en/arhiv>

© Национальная академия наук Республики Казахстан, 2020

Адрес редакции: 050100, г. Алматы, ул. Кунаева, 142,

Институт органического катализа и электрохимии им. Д. В. Сокольского,
каб. 310, тел. 291-62-80, факс 291-57-22, e-mail:orgcat@nursat.kz

Адрес типографии: «NurNaz GRACE», г. Алматы, ул. Рыскулова, 103.

Editor in chief

doctor of chemistry, professor, academician of NAS RK
M.Zh. Zhurinov

Editorial board:

Agabekov V.Ye. prof., academician (Belarus)
Volkov S.V. prof., academician (Ukraine)
Vorotyntsev M.A. prof., academician (Russia)
Gazaliyev A.M. prof., academician (Kazakhstan)
Yergozhin Ye.Ye. prof., academician (Kazakhstan)
Zharmagambetova A.K. prof. (Kazakhstan), deputy editor in chief
Zhorobekova Sh.Zh. prof., academician (Kyrgyzstan)
Itkulova Sh.S. prof. (Kazakhstan)
Mantashyan A.A. prof., academician (Armenia)
Praliyev K.D. prof., academician (Kazakhstan)
Bayeshov A.B. prof., academician (Kazakhstan)
Burkitbayev M.M. prof., academician (Kazakhstan)
Dzhusipbekov U.Zh. prof., corr. member (Kazakhstan)
Muldakhmetov M.Z. prof., academician (Kazakhstan)
Mansurov Z.A. prof. (Kazakhstan)
Nauryzbayev M.K. prof. (Kazakhstan)
Rudik V. prof., academician (Moldova)
Rakhimov K.D. prof., academician (Kazakhstan)
Streltsov Ye. prof. (Belarus)
Tashimov L.T. prof., academician (Kazakhstan)
Toderash I. prof., academician (Moldova)
Khalikov D.Kh. prof., academician (Tadzhikistan)
Farzaliyev V. prof., academician (Azerbaijan)

News of the National Academy of Sciences of the Republic of Kazakhstan. Series of chemistry and technology.

[ISSN 2518-1491 \(Online\)](#)

[ISSN 2224-5286 \(Print\)](#)

Owner: RPA "National Academy of Sciences of the Republic of Kazakhstan" (Almaty)

The certificate of registration of a periodic printed publication in the Committee of Information and Archives of the Ministry of Culture and Information of the Republic of Kazakhstan N 10893-Ж, issued 30.04.2010

Periodicity: 6 times a year

Circulation: 300 copies

Editorial address: 28, Shevchenko str., of. 219, 220, Almaty, 050010, tel. 272-13-19; 272-13-18,
<http://chemistry-technology.kz/index.php/en/arhiv>

© National Academy of Sciences of the Republic of Kazakhstan, 2020

Editorial address: Institute of Organic Catalysis and Electrochemistry named after D. V. Sokolsky
142, Kunayev str., of. 310, Almaty, 050100, tel. 291-62-80, fax 291-57-22,
e-mail: orgcat@mursat.kz

Address of printing house: «NurNaz GRACE», 103, Ryskulov str, Almaty.

NEWS

OF THE NATIONAL ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN
SERIES CHEMISTRY AND TECHNOLOGY

ISSN 2224-5286

<https://doi.org/10.32014/2020.2518-1491.4>

Volume 1, Number 439 (2020), 29 – 36

UDC 911.8

M.S. Yessenamanova¹, A. Shukbarov^{1,2}, V.F. Zaitsev²,
I.V. Melnik², Zh.S. Yessenamanova¹, A.E. Tlepbergenova¹

¹Kh.Dosmukhamedov Atyrau State University, Atyrau, Republic of Kazakhstan;

²Astrakhan State Technical University, Astrakhan, Russian Federation
mansiya.73@mail.ru, kinoman_1997@mail.ru, viacheslav-zaitsev@yandex.ru,
irina_1melnik@mail.ru, zhanyessen@mail.ru, anar_2808@mail.ru

ESTIMATION OF OIL PRODUCTS CONTENT IN SOIL AND WATER OBJECTS IN THE AREA OF LOCATION OF SLUDGE DRESSERS ON THE COAST OF THE VOLGA RIVER

Abstract. The article assesses the quantitative composition of petroleum products at oil waste storage areas near the confluence of the Volga River and its Kizan branch of the Volga Region of the Astrakhan Region. Studies were conducted of soil samples at different depths in two pits and groundwater, groundwater and bottom sediments. In the studied two wells, the maximum excess is observed from 104 to 260 times in the second well, while in the first well the oil content exceeds from 67.5 to 133 times. The content of heavy metals also exceeded the maximum permissible concentration, for example, total chromium 168 times and 2040 times and arsenic 1.7 times and 2.6 times, respectively, in the first and second wells. According to the results of groundwater research, the oil content exceeds 88 and 14.4 times for the 1st oil well and 520 and 86.6 times for the 2nd well. On the Volga River section, located at the 200th distance from the oil, the content of oil products in the water is lower than the MPC, however, far from the coast, the studied indicator is higher than the MPC for fishery reservoirs with a maximum at a distance of 1000 m from the second oil tank. The maximum content of petroleum products (18719.3 ± 4679.8 mg / kg) in bottom sediments was observed in the area of oil tank No. 2, which exceeded the control variant by more than 36 times. Research shows that the second hole is the most polluted.

Key words: oil pit, oil products, heavy metals, maximum permissible concentration, soil, groundwater, bottom sediments.

Introduction. The oil pits in Sokolovo at one time were intended for the storage of oil products, which were earthen excavations with sloping walls where they temporarily stored oil, kerosene, fuel oil and other oil products. To ensure stability along the sides, oil pits were furnished with wooden bars. When filling such a pit with oil, it was absorbed and filled with water in order to reduce the pit. At this time, the remains of the pipeline system pipe and the wooden fortifications of one of the Sokolovskoye oil fields remained. Then they were used to receive oily waste after from all oil bases in the Astrakhan region.

Sokolovo oil pits are located at the confluence of the Volga River and its Kizan branch. In the hydrographic network of the Volga delta, the main channel is distinguished - the watercourse of the largest category, as well as hoses, ducts, eric and banks, differing in morphometric and hydraulic characteristics. A characteristic type of delta watercourses are proranes - natural ones that occur when water breaks out from one flood to another and artificial ones created for water exchange and fish passage [1].

Administratively, the contaminated territory of the Sokolovo oil pit object is located in the Volga region of the Astrakhan region within the boundaries of the municipality of Tatarobashmakovsky Village Council on the lands of the settlement [2].

Methods. Laboratory tests of soil samples for the content of PAHs were carried out by the accredited laboratory of the Federal State Institution SevKasptekhmordirektsiya (PDN F 16.1: 2.2.3: 3.62-09).

Sample preservation method: freezing. Sample volume: 1.0 kg.

Measurement Method: IKS - spectrometric; HPLC

Determination of the mass fraction of NP in soil samples is carried out by IR spectrometry. The method is based on the extraction of NP from the soil with a solvent at room temperature. The concentration of hydrocarbons in a soil sample is determined by the optical density measured on an IR spectrometer.

Of the traditional solvents for the infrared region, carbon tetrachloride is most suitable, since it is most transparent in this area.

HPLC allows the simultaneous separation of complex samples into their constituent components, detecting most components, measuring the concentration of one or more compounds (depending on specific analytical tasks and the availability of standard samples) [3].

For the study, soil samples were taken of two oil disposal pits located in the Volga region of the Astrakhan region and water samples from both the shore and from the vessel and from bottom sediments.

Results and discussion. The results of laboratory tests of soil samples taken during the reconnaissance survey of the coastal strip are presented in table 1.

Table 1 - Contaminant content in soil

Name of pollutants	MPC _{soil} , mg / kg	UEC _{soil} sand / loam, mg / kg	The content of pollutants, mg / kg	
			oil pit number 1	oil pit number 2
Oil products		1000	from 67500 to 133000	from 104000 to 260000
HM (gross form):				
lead	32		up to 4,48	up to 5,98
copper		33/132	up to 8,27	up to 8,26
cadmium		0,5/2,0	up to 0,09	up to 0,09
nickel		20/80	up to 18,1	up to 18,1
zinc		55/220	up to 20,5	up to 20,6
common chrome (6+)	0,05	-	up to 8,38	up to 102,0
mercury	2,1		up to 0,027	up to 0,022
arsenic	2,0		up to 3,40	up to 5,3

The data in the table indicate that in the soil of the coastal strip of oil pit No. 1, the content of oil products exceeds the MEA (maximum estimated amount) by a minimum of 67.5, and a maximum of 133 times. For oil pit No. 2, this excess is from 104 to 260 times. Such indicators of oil products characterize the level of land pollution with chemicals as very high [4].

According to the calculation of the integral index of pollution Zc, according to the degree of pollution with chemicals, the coastal ground soils are classified as "dangerous" and "extremely dangerous". Sanitary regulations have recommended on such lands the implementation of measures to reduce pollution and the binding of toxicants in soils, the organization and monitoring of toxicants in soils, groundwaters and local water sources [5].

An important circumstance is the excess of MPC for such heavy metals as total chromium (168 times for oil pit No. 1 and 2040 times for oil pit No. 2) and arsenic (1.7 times for oil pit No. 1 and 2.6 times for oil pit No. 2). Due to the fact that the coastal strip is located 100m from the beach and is often visited by vacationers, fishing enthusiasts and local residents, this level of pollution poses a threat to human health. The problem is exacerbated by the destruction of the coast and the ingress of contaminated soil in the river Kizan, which is a source of centralized water supply and a reservoir of the highest category of fishery use, is a place of reproduction of fish stocks of the Volga-Caspian basin.

Given the highest excess concentration, a particular danger in this case is chromium. Despite the biological needs for it, its high concentrations are toxic. Chromium has a generally poisonous, irritating, cumulative, allergic, carcinogenic and mutagenic effect on the human and animal organism. According to published data, chromium is able to penetrate intact human skin in contact with an aqueous solution (hexavalent chromium in doses of 0.25; 0.025 and 0.005 mg / kg). Which leads to severe damage to the enzymatic system of the liver, with manifestations of embryotoxic and mutagenic effects [6]. In general, the data in the table indicate that the most polluted and therefore most dangerous is oil pit No. 2, which is located 10 meters from the residential development. At the end of it is the pumping station of the cottage village. This situation requires urgent decision-making in order to prevent environmental dangers to the local population.

In soils, oil and oil products cause deep, irreversible changes in the morphological, physical, physicochemical, and microbiological properties of soils, and with a strong and very strong degree of contamination, they can provoke significant changes in the soil profile, and as a result, loss of fertility and exclusion of the territory from agricultural use [7].

The figure shows that the maximum amount of oil products was noted in the second oil pit at a depth of 1 and 4 m. For the first oil pit, the highest content of oil products was recorded at a depth of 2 m.

Such indicators of oil products characterize the level of land pollution with chemicals as very high and medium [8].

According to the degree of pollution with chemicals, the soil is classified as "moderately dangerous" and "dangerous" [5].

Sanitary rules imply control over the content of pollutants in all environmental objects, including soil, surface and groundwater, and a list of measures to reduce their impact on vegetation [5].




Figure 1 - The content of petroleum products in soil at different depths

The indicators presented in the figure show that the most polluted oil products in depth is also oil pit No. 2.

The results of laboratory tests of groundwater selected during the drilling of engineering and geological wells are presented in table 2.

Table 2 - The content of petroleum products in groundwater

MPCAw, mg / dm ³ (reservoirs of fishery significance)	MPCw, mg / dm ³ (reservoirs of household and cultural and domestic water use)	Contaminant content, mg / dm ³	
		oil pit No. 1	oil pit No. 2
0,05	0,3	4,4	26,0

The standards for maximum permissible concentrations of pollutants in the water of fishery facilities are established by order of the Federal Agency for Fisheries dated January 18, 2010 No. 20.

The standards for maximum permissible concentrations of pollutants in the water of water bodies of domestic, drinking, and cultural and domestic water use (GN 2.1.5.1315-03) are established by the Resolution of the Chief State Sanitary Doctor of the Russian Federation of April 30, 2003. No. 78 [9].

The data in Table 2 indicate an excess of oil products in groundwater by 88 and 14.4 times for the 1st oil pit and 520 and 86.6 times for the 2nd oil pit, taking into account the fact that the Kizan River is both a fishery and household and cultural purposes.

It should be noted that the increased content of petroleum products in groundwater indicates their high migration activity. And since the unloading of groundwater occurs in the river Kizan there is a risk of these pollutants entering the river [10].

To determine the oil content in the water, samples were taken both from the shore and from the vessel. The results of laboratory tests of water samples are presented in table 3.

Table 3 - The content of petroleum products at various points of sampling

No.	Water sampling site	MPCAw, mg / dm ³ (reservoirs of fishery significance)	MPCw, mg / dm ³ (reservoirs of household and cultural and domestic water use)	Oil content in samples, mg / dm ³	
				ship samples (50m from the coast)	samples from the shore
1	River Volga upstream (200 m) from the river Kizan	0,05	0,3	0,02±0,02	-
2	River Volga downstream (200 m) from the river Kizan			0,03±0,02	-
3	River Kizan (beach, control)	0,05	0,3	0,06±0,02	0,06±0,02
4	oil pit No. 1			0,04±0,02	0,18±0,06
5	oil pit No. 2			0,05±0,02	0,21±0,07
6	500 m downstream			0,05±0,02	0,13±0,04
7	1000 m downstream			0,03±0,01	0,28±0,10

The results of the table indicate that in the Volga River, located at the 200th distance from the oil industry, the content of oil products in the water is below the MPC. But already in the control, both offshore and far from it, this indicator exceeds the MPC for fishery reservoirs by 0.01 mg / dm³ and has the same values for both samples (0.06 ± 0.02 mg / dm³).

In further samples, the results are dramatically different depending on the sampling points. The coastal part is characterized by an excess of the studied indicator relative to the MPC value for reservoirs of fishery value with a maximum at a distance of 1000m downstream from the 2nd oil well. For samples 50m from the coast, the situation is more favorable, since the content of petroleum products meets the standards.

Thus, the research results indicate the direct impact of Sokolovo oil on water pollution by oil products near the coast of the Kizan branch.

An important indicator of the ecological state of the catchment is the chemical composition of bottom sediments. Bottom river deposits, accumulating and concentrating petroleum hydrocarbons, resins, heavy metals, are a representative indicator of pollution. Knowledge of the natural concentrations of heavy metals in the bottom sediments of rivers makes it possible to judge the state of their purity or contamination [11]. The results of laboratory tests of samples of bottom sediments taken from the vessel by the grab bottom grab DG-0.16 are presented in table 4.

Table 4 - The content of petroleum products in bottom sediments at various points of sampling

No	Sampling point	Petroleum products, mg / kg
1	River Kizan (beach, control)	513,9±128,5
2	oil pit No. 1	14994,5±3748,6
3	oil pit No. 2	18719,3±4679,8
4	500 m downstream	807,7±201,9
5	1000 m downstream	474,8±118,7

As can be seen from the table, the maximum content of petroleum products (18719.3 ± 4679.8 mg/kg) in bottom sediments was observed in the area of oil pit No. 2, which exceeded the control variant by more than 36 times. The minimum value (474.8 ± 118.7 mg / kg) was recorded at a distance of 1000 m downstream from the test object, and in the control (beach) the value of this indicator was slightly higher ($P < 0.05$).

Thus, a gradual increase in pollution of bottom sediments by oil products from control to oil pit No. 2 is observed, after which the picture changes in the direction of decreasing this indicator. Consequently, there is a clear dependence of the impact of Sokolovo oil on pollution of bottom sediments by oil products of the adjacent water area.

Conclusion. The petroleum product indices at oil pit No. 1 (from 67500 to 133000 mg / kg) and No. 2 (from 104000 to 260,000 mg / kg) characterize the level of land pollution with chemicals as very high.

The maximum content of oil products is observed in the second oil pit at a depth of 1 and 4 m (51400 and 46100 mg / kg, respectively). For the first oil pit, the highest content of oil products was recorded at a depth of 2 m (13000 mg / kg), which characterizes the level of land pollution with chemicals as very high and medium [12].

At the Volga River, located 200th from oil, the oil content in the water is below the MPC, although this indicator exceeds the MPC for fishery reservoirs by 0.01 mg / dm³ and has the same values for both samples (0.06 ± 0.02 mg / dm³). Away from the coast, the studied indicator is characterized by an excess relative to the MPC value for reservoirs of fishery value with a maximum at a distance of 1000 m from the 2nd oil pit. For samples from water (from a vessel), the content of petroleum products meets the standards.

The content of oil products in groundwater is 88 and 14.4 times higher than those for first oil pit and 520 and 86.6 times for second oil pit, taking into account the fact that the Kizan River is a reservoir of fishery, household and cultural purposes [13].

The maximum content of petroleum products (18719.3 ± 4679.8 mg / kg) in bottom sediments was observed in the area of oil pit No. 2, which exceeded the control variant by more than 36 times. The minimum value (474.8 ± 118.7 mg / kg) was recorded at a distance of 1000 m downstream from the test object.

**М.С. Есенаманова¹, А. Шукбаров^{1,2}, В.Ф. Зайцев²,
И.В. Мельник², Ж.С. Есенаманова¹, А.Е. Тлепбергенова¹**

¹Х.Досмұхамедов атындағы Атырау мемлекеттік университеті, Атырау, Казақстан Республикасы;
²Астрахань мемлекеттік техникалық университеті, Астрахань, Ресей Федерациясы

**ЕДІЛ ӨЗЕНІНІң ЖАГАЛАУЫНДА ҚАЛДЫҚТЫ ТОҒАНДА ОРНАЛАСҚАН АЙМАҚТА
ТОПЫРАҚ ЖӘНЕ СУ ОБЪЕКТИЛЕРИНДЕ МҰНАЙ ӨНІМДЕРІНІҢ ҚУРАМЫН БАГАЛАУ**

Аннотация. Мақалада Еділ өзені мен Астрахань облысының Еділ бойындағы Кизан тармағының жаңындағы мұнай қалдықтары қоймаларындағы мұнай өнімдерінің сандық құрамы бағаланады. Соколоводағы шұңқырлар бір кездері мұнай, керосин, мазут және басқа да мұнай өнімдерін уақытша сақтайтын көлбесу қабыргалары бар жер қазбалары болған мұнай өнімдерін сақтауға арналған. Топырақ үлгілерін зерттеу екі шұңқырда және жер асты суларында, жер асты сулары мен тубіндегі шөгінділерде әртүрлі тереңдікте жүргізілді. Зерттелген екі ұнғыманың екінші ұнғымада максималды жоғарылау 104-тен 260 есеге дейін, ал бірінші ұнғымада мұнайдың мөлшері 67,5-тен 133-ке дейін байқалды. Сондай-ақ, ауыр металдардың құрамы шекті рауалды мөлшерден асып кетті, мысалы, жалпы хром 168 есе және 2040 есе, мышьяк 1,7 есе және бірінші ұнғымаларда сәйкесінше 2,6 есе. Бұл жағдайда ең қауіпті - бұл хром, ол улы, тітіркендіріш, кумулятивті, аллергиялық, канцерогендік және мутагендік эсерге ие. Топырақтағы мұнай өнімдерінің мөлшері екінші ұнғымада 1 м тереңдікте 51400 мг / кг-ға дейін және 4 м тереңдікте - 461000 мг/кг дейін жоғарылауымен сипатталады, сонымен қатар жер бетінде мұнай өнімдерінің мөлшері 15000 мг / кг, 2 метр тереңдікте 27000 мг / кг, 6 м тереңдікте - 20 000 мг / кг тең. Алғашкы мұнай құятын ыдыста 2 м тереңдігі 13000 мг / кг мұнай өнімдерінің ең көп мөлшері сипатталады, бұл 2 мұнай құятын қоймадағы ең көп мөлшерден 3 есе төмен. 1 және 3 метр тереңдікте майдың мөлшері 2000 мг / кг құрайды, басқа тереңдікте - 0, 4, 5, 6, 7, 8, 9, 10 метр, олар 1000 мг / кг-дан аз. Екінші мұнай резервуарында 2000 мг / кг-нан төмен топырақтағы мұнай өнімдерінің құрамы тек 7-ден 10 метр тереңдікте болады.

Жер асты суларын зерттеу нәтижелері бойынша мұнайдың құрамы 1-ші ұнғыма үшін 88 және 14,4 еседен, ал 2-ші ұнғымадан 520 және 86,6 еседен асады. Жер асты суларындағы мұнай өнімдерінің жоғарылауы олардың көші-қон белсенділігінің жоғары екендігін көрсетеді. Өзенде жер асты суларының түсі орын алады. Кизанда осы ластаушы заттардың өзенге ену қаупі бар. Мұнай өнеркәсібінен 200-кашықтықта орналасқан Волга өзенінің участасеінде судағы мұнай мөлшері ШРМ-нен төмен, дегенмен, жағалаудан алыс жерде, зерттелген көрсеткіш 2-ші мұнай резервуарынан максималды 1000 м қашықтықта балық аулау су қоймалары үшін ШРМ мәнінен жоғары. Төменгі шөгінділердегі мұнай өнімдерінің максималды мөлшері ($18719,3 \pm 4679,8$ мг / кг) №2 мұнай резервуарының аумағында байқалды, бұл бақылау нұсқасынан 36 есе асып түсті. Ең төменгі мәні ($474,8 \pm 118,7$ мг / кг) сынақ объектісінен 1000 м қашықтықта тіркелді, ал бақылауда (жагажайда) бұл көрсеткіш шамалы жоғары болды ($P < 0.05$). Осылайша, мұнай шөгінділерінің мұнай өнімдерімен бақылаудан №2 мұнай резервуарына дейін ластануының біртіндеп артуы байқалады, содан кейін көрініс осы көрсеткіштің төмендеуіне карай өзгереді. Демек, Соколовское мұнайының әсер етуінің түбіндегі шөгінділерді іргелес су аймағының мұнай өнімдерімен ластануына айқын тәуелділігі бар.

Корытындылай келе, зерттеу нәтижелері №1 мұнай кеніштеріндегі мұнай өнімдерінің көрсеткіштері (67,500-ден 133 000 мг / кг-ға дейін) және №2 (104 000-нан 260 000 мг / кг-ға дейін) жердің химиялық заттармен ластану деңгейінің өте жоғары екенін сипаттайтыны. Мұнай өнімдерінің ең көп мөлшері екінші мұнай кенішінде 1 және 4 м терендікте байкалады (сайкесінше 51400 және 46100 мг / кг). Алғашкы мұнай резервуарда мұнай өнімдерінің ең жоғары мөлшері 2 м (13000 мг / кг) терендікте тіркелді, бұл жердің химиялық заттармен ластану дәрежесін өте жоғары және орташа деп сипаттайтыны. Мұнайдан 200-ші жерде орналасқан Волга өзенінің суында мұнай құрамы ШРМ-ден төмен, дегенмен бұл көрсеткіш балық шаруашылығы су айдындары үшін ШРМ-ден $0,01 \text{ mg} / \text{dm}^3$ -ге асады және екі үлгі үшін де бірдей ($0,06 \pm 0,02 \text{ mg} / \text{dm}^3$). Кизан өзенінің балық шаруашылығы, тұрмыстық және мәдени мақсаттағы су қоймасы болғандылығын ескере отырып, жер асты суларындағы мұнай өнімдерінің мөлшері бірінші мұнай кенішіне карағанда 88 және 14.4 есе, 2 резервуарда 520 және 86,6 есе жоғары.

Төмөнгі шөгінділердегі мұнай өнімдерінің максималды мөлшері ($18719,3 \pm 4679,8$ мг / кг) №2 мұнай резервуарының аумағында байқалды, бұл бақылау нұсқасынан 36 есе асып түсті. Ең төмөнгі мәні ($474,8 \pm 118,7$ мг / кг) сынақ объектісінен 1000 м қашықтықта тіркелді. Зерттеу нәтижелері екінші ұнғыманың ең көп ластанғанын көрсетеді.

Түйін сөздер: мұнайқалдықты тоған, мұнай өнімдері, ауыр металдар, шекті рауалды мөлшер, топырақ, жер асты сулары, су түбіндегі шөгінділер.

**М.С.Есенаманова¹, А.Шукбаров^{1,2}, В.Ф.Зайцев²,
И.В.Мельник², Ж.С.Есенаманова¹, А.Е.Тленбергенова¹**

¹Атырауский государственный университет имени Х.Досмухamedова;

² Астраханский государственный технический университет, Астрахань, Российская Федерация

ОЦЕНКА СОДЕРЖАНИЯ НЕФТЕПРОДУКТОВ В ПОЧВЕННЫХ И ВОДНЫХ ОБЪЕКТАХ В РАЙОНЕ РАСПОЛОЖЕНИЯ ШЛАМОНАКОПИТЕЛЕЙ НА ПОБЕРЕЖЬЯХ РЕКИ ВОЛГА

Аннотация. В статье дана оценка по количественному составу нефтепродуктов в местах хранения отходов нефти в районе слияния реки Волга и ее рукава Кизань Приволжского района Астраханской области. Нефтяные ямы в Соколово в свое время были предназначены для хранения нефтепродуктов, представляющие собой земляные выемки с наклонными стенками, где временно хранили нефть, керосин, мазут и прочие нефтепродукты. Были проведены исследования проб почвы на разных глубинах в двух ямах и подземных, грунтовых вод и донных отложений. В исследуемых двух ямах отмечается максимальное превышение от 104 до 260 раз во второй яме, тогда как в первой яме содержание нефтепродуктов превышает от 67,5 до 133 раз. По содержанию тяжелых металлов также отмечается превышение предельно-допустимой концентрации, например, по хрому общему в 168 раз и в 2040 раз и по мышьяку в 1,7 раз и 2,6 раз соответственно в первой и второй ямах. Наиболее опасным при этом является хром, который очень токсичен, оказывая отравляющее, раздражительное, кумулятивное, аллергическое, канцерогенное и мутагенное действие. Содержание нефтепродуктов в почве характеризуется повышенным содержанием во второй яме на глубине 1 м до 51400 мг/кг и на глубине 4 м – 461000 м. При этом на поверхности земли содержание нефтепродуктов составляет 15000 мг/кг, на глубине 2 метров 27000 мг/кг, на глубине 6 м – 20000 мг/кг. В первой нефтеяме самым максимальным содержанием нефтепродуктов характеризуется глубина 2 м с 13000 мг/кг, что более чем в 3 раза ниже максимального содержания во 2 нефтеяме. На глубине 1 и 3 метров содержание нефтепродуктов составляет около 2000 мг/кг, на других глубинах – 0, 4, 5, 6, 7, 8, 9, 10 метрах они составляют менее 1000 мг/кг. Во второй нефтеяме содержание нефтепродуктов в почвогрунте ниже 2000 мг/кг характерно только на глубинах от 7 до 10 метров.

По результатам исследований подземных вод содержание нефтепродуктов превышает в 88 и 14,4 раз для 1-ой нефтеямы и 520 и 86,6 раз для 2-ой ямы. Повышенное содержание нефтепродуктов в грунтовых водах говорит о высокой их миграционной активности. И так как разгрузка грунтовых вод происходит в р. Кизань, существует угроза попадания этих загрязнений в реку. На участке р.Волга, находящейся в 200-ом отдалении от нефтеям, содержание нефтепродуктов в воде ниже ПДК, однако **вдали от берега характерно превышение исследуемого показателя относительно значения ПДК для водоемов рыбохозяйственного значения с максимумом на расстоянии 1000м от 2-ой нефтеямы.** Максимальное содержание нефтепродуктов (**18719,3±4679,8 мг/кг**) в донных отложениях отмечалось в районе нефтеям №2, что превосходило контрольный вариант более чем в 36 раз. Минимальное значение (**474,8±118,7 мг/кг**) было зарегистрировано на расстоянии 1000м по течению от исследуемого объекта, причем в контроле (пляж) величина данного показателя была несколько выше ($P < 0,05$). Таким образом, наблюдается постепенное нарастание загрязнения донных отложений нефтепродуктами от контроля до нефтеям №2, после чего картина меняется в сторону снижения данного показателя. Следовательно, прослеживается четкая зависимость воздействия Соколовских нефтеям на загрязнение донных отложений нефтепродуктами прилегающей водной площади.

В заключении, результаты исследований показывают, что показатели содержания нефтепродуктов на нефтеямах №1 (от 67500 до 133000мг/кг) и №2 (от 104000 до 260000мг/кг) характеризуют уровень загрязнения земель химическими веществами как очень высокий. Максимальное содержание нефтепродуктов наблюдается во второй нефтеяме на глубине 1 и 4 м (51400 и 46100 мг/кг, соответственно). Для первой нефтеямы наибольшее содержание нефтепродуктов зарегистрировано на глубине 2м (13000 мг/кг), что характеризует уровень загрязнения земель химическими веществами как очень высокий и средний. На участке р.Волга, находящейся в 200-ом отдалении от нефтеям, содержание нефтепродуктов в воде ниже ПДК, хотя данный показатель превышает ПДК для водоемов рыбохозяйственного значения на 0,01 мг/ дм³ и имеет для обеих проб одинаковые значения (**0,06±0,02 мг/дм³**). Содержания нефтепродуктов в подземных водах в 88 и 14,4 раз превышают таковые для 1 нефтеямы и 520 и 86,6 раз для 2 ямы с учетом того, что р.Кизань является как водоемом рыбохозяйственного, так хозпитьевого и культурно-бытового назначения [13].

Максимальное содержание нефтепродуктов (**18719,3±4679,8 мг/кг**) в донных отложениях отмечалось в районе нефтеям №2, что превосходило контрольный вариант более чем в 36 раз. Минимальное значение (**474,8±118,7 мг/кг**) было зарегистрировано на расстоянии 1000м по течению от исследуемого объекта. Результаты исследований показывают, что наиболее загрязненной является вторая яма.

Information about the authors:

Yessenamanova Mansiya, candidate of Technical Sciences, Kh.Dosmukhamedov Atyrau State University, Atyrau, Kazakhstan; mansiya.73@mail.ru; <https://orcid.org/0000-0002-5423-2857>;

Shukbarov Askar, undergraduate student of joint educational program, Kh.Dosmukhamedov Atyrau State University, Atyrau, Kazakhstan, Astrakhan State Technical University, Astrakhan, Russia; kinoman_1997@mail.ru, <https://orcid.org/0000-0002-3642-6121>;

Zaitsev Vyacheslav, doctor of Agricultural Sciences, Astrakhan State Technical University, Astrakhan, Russia; viacheslav-zaitsev@yandex.ru, <https://orcid.org/0000-0001-6350-2129>;

Melnik Irina, candidate of Biological Sciences Astrakhan State Technical University, Astrakhan, Russia; irina_1melnik@mail.ru, <https://orcid.org/0000-0002-6925-6835>;

Yessenamanova Zhanar, master of Engineering and Technology "Applied ecology", doctoral candidate of the PhD "Ecology" of Kh.Dosmukhamedov Atyrau State University, Atyrau, Kazakhstan; zhanyessen@mail.ru, <http://orcid.org/0000-0003-3868-4092>;

Tlepbergenova Anar, candidate of Pedagogical Sciences, Kh.Dosmukhamedov Atyrau State University, Atyrau, Kazakhstan; anar_2808@mail.ru, <http://orcid.org/0000-0001-7373-8944>

REFERENCES

- [1] Guryeva M.S.. (2010) Geocological problems of the quality of water resources and their rational use (on the example of the Astrakhan region) [Geoekologicheskie problemy kachestva vodnyh resursov i ih racional'nogo ispol'zovaniya (na primere Astrahanskoy oblasti)] // Abstract of dissertation for the degree of candidate of geographical sciences. Astrakhan. P. 28 <http://www.dislib.ru/zemlya/106495-1-geoekologicheskie-problemi-kachestva-vodnih-resursov-ih-racionalnogo-ispolzovaniya-na-primere-astrahanskoy-oblasti.php> (In Russian)
- [2] Melnik I.V., Drozdova A.E. (2017) Analysis of the current state of terrestrial vegetation in the territory of Sokolovsky oil pits in the Astrakhan region [Analiz sovremenennogo sostojaniya nazemnoj rastitel'nosti na territorii Sokolovskikh neftjanyh jam v Astrahanskoy oblasti] // Political Internet electronic scientific journal of the Kuban State Agrarian University. Vol.131(07). <http://ej.kubagro.ru/2017/07/pdf/86.pdf> (In Russian)
- [3] Egazaryants S.V., Karakhanova N.K. (2009) Determination of aromatic hydrocarbons in jet fuels by capillary gas and high performance liquid chromatography [Opredelenie aromaticeskikh uglevodorodov v reaktivnyh toplivah metodami kapilljarnoj gazovoj i vysokojeffektivnoj zhidkostnoj hromatografii] // Bulletin of Moscow University. Ser. 2. Chemistry. Vol. 50 (1). P. 40-6 (In Russian)
- [4] The procedure for determining the extent of damage from land pollution by chemical substances (approved by Roskomzem on 10.11.1993 and the Ministry of Natural Resources of the Russian Federation on 18.11.1993) [Porjadok opredelenija razmerov ushherba ot zagrjaznenija zemel' himicheskimi veshhestvami (utv. Roskomzemom 10.11.1993 g. i Minprirody RF 18.11.1993 g.)] Moscow, Russia, 1993 (In Russian)
- [5] SanPiN 2.1.7.1287-03 Sanitary and epidemiological requirements for soil quality (approved by the Decree of the Chief State Sanitary Doctor of the Russian Federation of April 17, 2003 No. 53.) [SanPiN 2.1.7.1287-03 Sanitarno-jevidemiologicheskie trebovaniya k kachestvu pochvy (utv. postanovleniem Glavnogo gosudarstvennogo sanitarnogo vracha RF ot 17.04.2003 g. №53.)] Moscow, Russia, 2003 (In Russian)
- [6] Smirnov M.I. (1984) Comparative hygienic assessment of the toxicity and danger of chromium ions in water, taking into account the impact on the development of experimental atherosclerosis [Sravnitel'naja gigienicheskaja ocenka toksichnosti i opasnosti ionov hroma v vode s uchetom vlijaniya na razvitiye eksperimental'nogo ateroskleroza] // Abstract of dissertation for the degree of candidate of medical sciences. Moscow. P. 20. (In Russian)
- [7] Орлов Д.С., Малинина М.С., Мотузова Г.В. (2001) Chemical pollution of soils and their protection: Dictionary-reference [Himicheskoe zagrjaznenie pochv i ih ohrana: Slovar'-spravochnik]. Moscow: Agropromizdat. P. 303 (In Russian)
- [8] Mamedova S. (2019) Environmental assessment of the lankaran zone soils [Ekologicheskaja ocenka pochv lenkoranskoj zony] // Sciences about the earth. Vol. 5 (4): 175-183. <https://doi.org/10.33619/2414-2948/41/21> (In Russian)
- [9] GN 2.1.5.1315-03 Standards for maximum permissible concentrations of pollutants in the water of water bodies for drinking, domestic and cultural water [GN 2.1.5.1315-03 Normativny predel'no dopustimyh koncentracij zagrjaznjushhih veshhestv v vode vodnyh ob#ektov hozjajstvenno-pit'evogo i kul'turno-bytovogo vodopol'zovaniya (utv. postanovleniem Glavnogo gosudarstvennogo sanitarnogo vracha RF ot 30.04.2003g. №78.)] Moscow, Russia, 2003 (In Russian)
- [10] Kalimanova D.Zh., Kalimukasheva A.D., Kubasheva J.A., Nazhetova A.A. (2019) Features of hydrochemical and geochemical indicators of the North-eastern part of the Caspian sea (zones, oil and gas fields of the Kazakhstan sector) // News of the National academy of sciences of the Republic of Kazakhstan. Series chemistry and technology. 1 (433): ISSN 2224-5286 <https://doi.org/10.32014/2019.2518-1491.4>
- [11] Nadirov K.S., Cherkava G.V., Chikhonadskikh E.A., Makkaveeva N.A., Sadyrbaeva A.S., Orymbetova G.E. (2018) Analysis of influence of emissions of harmful substances with exhaust gases of marine dual fuel internal combustion engine on the environment and human health // News of the National academy of sciences of the Republic of Kazakhstan. Series chemistry and technology. 6 (432): ISSN 2224-5286 <https://doi.org/10.32014/2018.2518-1491.36>
- [12] Mustafaev Zh. S., Kozykeeva A. T., Zhanymkhan K., Aldiyarova A. E., Mosie Józef (2019) The methods of assessment of maximum allowable impacts ecologically on small rivers // N E W S OF News of the National academy of sciences of the Republic of Kazakhstan. Series of geology and technical sciences. 2(434): 30 – 38. ISSN 2518-170X (Online), ISSN 2224-5278 (Print). <https://doi.org/10.32014/2019.2518-170X.35>
- [13] Sainova G. A., Akbasova A. D., Abdikarim G. G., Kalieva N. A., Ali Ozler Mehmet 2019 Environmental monitoring on the landfill of solid domestic wastes of the town Kentau // News of the National academy of sciences of the Republic of Kazakhstan. Series of geology and technical sciences. 1(433): 57 – 62. ISSN 2518-170X (Online), ISSN 2224-5278 (Print). <https://doi.org/10.32014/2019.2518-170X.6>

Publication Ethics and Publication Malpractice in the journals of the National Academy of Sciences of the Republic of Kazakhstan

For information on Ethics in publishing and Ethical guidelines for journal publication see <http://www.elsevier.com/publishingethics> and <http://www.elsevier.com/journal-authors/ethics>.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis or as an electronic preprint, see <http://www.elsevier.com/postingpolicy>), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyright-holder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct (http://publicationethics.org/files/u2/New_Code.pdf). To verify originality, your article may be checked by the Cross Check originality detection service <http://www.elsevier.com/editors/plagdetect>.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.

Правила оформления статьи для публикации
в журнале смотреть на сайте:

www:nauka-nanrk.kz

<http://chemistry-technology.kz/index.php/en/arhiv>

[ISSN 2518-1491 \(Online\)](#), [ISSN 2224-5286 \(Print\)](#)

Редакторы: *М. С. Ахметова, Г. Б. Халидуллаева, Д. С. Аленов*
Верстка на компьютере *А.М. Кульгинбаевой*

Подписано в печать 13.02.2020.
Формат 60x881/8. Бумага офсетная. Печать – ризограф.
7,8 п.л. Тираж 300. Заказ 1.

*Национальная академия наук РК
050010, Алматы, ул. Шевченко, 28, т. 272-13-18, 272-13-19*